

PCT


WORLD INTELLECTUAL PROPERTY ORGANIZATION  
International Bureau

## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<b>(51) International Patent Classification <sup>6</sup> :</b> <b>F25D 13/06, 25/04, 3/11, B65G 17/06, A23L 3/36</b>	<b>A1</b>	<b>(11) International Publication Number:</b> <b>WO 99/57496</b> <b>(43) International Publication Date:</b> 11 November 1999 (11.11.99)
<b>(21) International Application Number:</b> PCT/SE99/00735 <b>(22) International Filing Date:</b> 4 May 1999 (04.05.99) <b>(30) Priority Data:</b> 09/073,247      6 May 1998 (06.05.98)      US <b>(71) Applicant:</b> FRIGOSCANDIA EQUIPMENT AB [SE/SE]; P.O. Box 913, S-251 09 Helsingborg (SE). <b>(72) Inventor:</b> PÅHLSSON, Sten; Frostgatan 222, S-260 35 Ödåkra (SE). <b>(74) Agent:</b> AWAPATENT AB; P.O. Box 5117, S-200 71 Malmö (SE).	<b>(81) Designated States:</b> AE, AL, AM, AT, AT (Utility model), AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, CZ (Utility model), DE, DE (Utility model), DK, DK (Utility model), EE, EE (Utility model), ES, FI, FI (Utility model), GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SK (Utility model), SL, TJ, TM, TR, TT, UA, UG, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).  <b>Published</b> <i>With international search report.          Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>	

**(54) Title:** APPARATUS FOR AIR-TREATMENT OF PRODUCTS**(57) Abstract**

An apparatus for air-treatment of products comprises an endless conveyor belt following through part of its length a helical path forming a stack of tiers. Side plates at one longitudinal edge of the conveyor belt form an outer cylinder wall delimiting the stack radially outwards. An inner cylinder wall delimits the stack radially inwards. Thereby, a central space is defined by the inner cylinder wall and an annular space is defined between the outer cylinder wall and the inner cylinder wall. An end closure substantially adjoins the outer cylinder wall at one end of the stack. Means are provided for blowing air through the central space towards the end closure and back through the annular space between the outer and inner cylinder walls for air-treatment of products carried by the conveyor belt in the helical path. The air is conditioned and blown through the annular space between the outer and inner cylinder walls.



**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

APPARATUS FOR AIR-TREATMENT OF PRODUCTS

The present invention relates to air-treatment of products, primarily food products and the like, using appropriately conditioned air.

The prior art includes several types of apparatuses  
5 for such treatment where the conditioned air is substantially different from the air surrounding the apparatus. Therefore, it is important that the conditioned air is recirculated within the apparatus, i.e. the apparatus should be as air-tight as possible and this  
10 often makes the apparatus complex and expensive.

When the difference between the conditioned air and the surrounding air is not very extreme, a less complicated apparatus would be preferable.

The object of the present invention is to provide a  
15 simple and cost-effective apparatus for air-treatment of products, such as cooling and proofing.

This object is achieved with an apparatus which comprises an endless conveyor belt following through part of its length a helical path forming a stack of tiers;  
20 side plates at one longitudinal edge of the conveyor belt forming an outer cylinder wall delimiting the stack radially outwards; means forming an inner cylinder wall delimiting the stack radially inwards, whereby a central space is defined by the inner cylinder wall and an  
25 annular space is defined between the outer cylinder wall and the inner cylinder wall; an end closure substantially adjoining the outer cylinder wall at one end of the stack; means for blowing air through the central space towards the end closure and back through the annular  
30 space between the outer and inner cylinder walls for air-

treatment of products carried by the conveyor belt in the helical path; and means for conditioning the air to be blown through said space between the outer and inner cylinder walls.

5 By this design, the outer cylinder wall also forms the single peripheral wall of the apparatus which therefore does not need any separate housing. This means a major cost reduction. The fact that the outer cylinder wall may not form a perfect air-tight wall is of less  
10 importance when the influence of the conditioning means on the air, e.g. for heating or cooling the air or for adjusting its humidity, is not very substantial.

In a first embodiment of the apparatus according to the invention, the end of the central space opposite to  
15 the end closure is closed except for an inlet to the air-blowing means. Thus, air is sucked into the apparatus from the environment by the air-blowing means and is returned to the environment, preferably at an open end of the annular space opposite to the end closure, after  
20 having passed first through the conditioning means and then through the annular space where the products to be treated are carried by the conveyor belt along the helical path. In this embodiment, the conditioning means is positioned in the central space within the inner  
25 cylinder wall.

Alternatively, the conditioning means may be positioned outside a room accommodating the apparatus, wherein the room has an inlet from the conditioning means and an outlet.

30 In a further embodiment, the apparatus comprises a further end closure substantially adjoining the outer cylinder wall at the other end of the stack, whereby air is blown in a substantially closed path. In this embodi-

ment, the conditioning means may be positioned in the inner space within the inner cylinder wall or may be positioned in the further end closure.

FIG. 1 is a schematic perspective view illustrating a belt conveyor of the prior art.

FIG. 2-5 are schematic side views of four embodiments of an apparatus for air-treatment of products according to the present invention.

A belt conveyor of the type shown in FIG. 1 has a conveyor belt 1 adapted to follow, in the manner illustrated, through part of its length a path comprising a number of superimposed helically extending tiers forming a stack 2. The illustrated conveyor belt 1 comprises a number of mutually articulated links and can run straight and in curves upwards, downwards and sideways.

Each link comprises a bottom part 3 and a spacer 4 at least at the outer longitudinal side 5 of the conveyor belt 1, as seen in the stack 2. Each link may have a spacer 4 also at the inner longitudinal side 6 of the conveyor belt 1. The spacers 4 of an underlying tier in the stack 2 engage and support the corresponding side edge of an overlying tier. Thereby, the spacers 4 at the outer longitudinal side of the conveyor belt 1 in the stack 2 form an outer cylinder wall 7, and the spacers 4 at the inner longitudinal side of the conveyor belt 1 in the stack 2 form an inner cylinder wall 8, such that an annular space 9 is formed between the outer cylinder wall 7 and the inner cylinder wall 8. A cylindrical central space 10 is formed within the inner cylinder wall 8.

As an alternative to the inner cylinder wall 8 formed by spacers 4, the inner cylinder wall may comprise a wall separate from the conveyor belt 1, e.g. a wall formed on the outer periphery of a drum used for support-

ting the conveyor belt at its inner longitudinal side in the stack.

In both alternatives, the annular space 9 is used as a channel for blowing air past products carried by the conveyor belt 1. Normally, the air is blown vertically through the annular space 9 to cool or heat the products or to change the moisture content of the products.

The alternative types of conveyor belts referred to above are described more in detail in U.S. Patents Nos. 3,938,651; 4,565,282; 4,875,343; 4,941,567; 5,031,751; and 5,226,291, which all are incorporated herein by reference. Further, these conveyor belts may be combined with several types of supporting and/or driving means found in the prior art. Some of these supporting and/or driving means also are described in the above referenced patents.

The above described conveyor belts may be used in an apparatus for air-treatment of products according to the present invention, as illustrated in FIGS. 2-5. In these Figures, the conveyor belt 1 is illustrated very schematically as a stack 2 of tiers and those parts of the conveyor belt 1 which are outside the stack 2 are not shown. Further, the conveyor belt used has preferably spacers 4 at both longitudinal sides such that the stack 2 is self-supported except for the lowest tier.

The embodiment illustrated in FIG. 2 comprises the stack 2 and a top cover 11 which constitutes an end closure substantially adjoining the outer cylinder wall 7 at the top end of the stack 2. Further, a horizontal partition 12 is positioned near the bottom of the central space 10 adjoining to the inner cylinder wall 8. This partition 12 closes the central space 10 at its lower end except for an inlet to a fan 13 which constitutes a means

for blowing air from outside the stack 2 upwards through the central space 10 against the top cover 11 where the flow of air is redirected down through the annular space 9 from the top end to the bottom end thereof. The annular space 9 is open at its bottom end so that the air blown through the annular space 9 can escape at that end. As shown in FIG. 2, the air sucked in by the fan 13 is passed through a cooler 14 and/or a heater 15 and/or is passed by a steam generator 16 so as to condition the air before its passing down through the annular space 9.

The above described configuration is useful when the required air velocity is not too high, e.g. less than about 2 m/s, and also when the conditioning of the air to be blown through the annular space 9 is not very substantial, e.g. the required temperature decrease/increase generated by the cooler 14/heater 15 and/or the humidity increase obtained through the steam generator 16. As illustrated by arrows 17 directed from the inside of the inner cylinder wall 8 through the stack 2 to the outside of the outer cylinder wall 7 neither one of these walls 7 and 8 need to be perfectly tight. Thus, it is possible to use a conveyor belt of the types described above being self-supported at least at its outer edge in the stack 2 and, preferably, being self-supported also at its inner peripheral edge in the stack 2.

The arrangement supporting the conveyor belt 1 and the top closure 11 in FIG.1 is not illustrated but are obvious to the man skilled in the art. However, it should be noted that the stack 2 formed by the conveyor belt 1 is continuously revolving while the top closure 11 is stationary.

The embodiment illustrated in FIG. 3 differs from the one illustrated in FIG. 2 in that a skirt 18

surrounds the lower end of the apparatus and forms a closure adjoining the bottom end of the outer cylinder wall 7 and the floor beneath the apparatus. Thereby, the air blown up through the central space 10, down through the annular space 9 and out of the bottom open end of the annular space 9 is recirculated by being sucked into the fan 13. Of course, this skirt 18 is much simpler and cheaper than the housing normally used in the prior art apparatus, as exemplified in the references cited above.

10 The embodiment illustrated in FIG. 4 uses double skirts, i.e. a first skirt 19 corresponding to the skirt 18 in the embodiment illustrated in FIG. 3 and a second skirt 20 adjoining the bottom end of the inner cylinder wall 8 and the floor beneath the apparatus. As a result, 15 a chamber 21 is formed below the stack 2. This chamber 21 has a first opening that coincides with the bottom opening of the annular space 9 and a second opening towards the central space 10 within the inner cylinder wall 8. More precisely, the fan 13 and the conditioning means comprising a cooler 14 and/or a heater 15 and/or a 20 steam generator 16, are inserted between the second opening and the lower end of the central space 10. As a consequence of the opening in the chamber towards the conditioning means, no partition is necessary at the 25 lower end of the central space 9.

Finally, FIG. 5 illustrates a further embodiment of the apparatus according to the present invention which is identical with the embodiment illustrated in FIG. 2 except that the conditioning means is positioned outside 30 a room 22 which accommodates the rest of the apparatus. The room 22 has a bottom inlet 23 connected to the conditioning means (not shown) and a top outlet 24 for expelling surplus air.



It goes without saying that the invention is not restricted to the embodiments described above, and that a variety of modifications is possible within the scope of the invention as defined in the appended claims. Thus,  
5 the means forming the inner cylinder wall may be separate from the conveyor belt, e.g. comprise a central drum.

## CLAIMS

1. An apparatus for air-treatment of products,  
5 comprising  
    an endless conveyor belt following through part of  
    its length a helical path forming a stack of tiers;  
    side plates at one longitudinal edge of the conveyor  
belt forming an outer cylinder wall delimiting the stack  
10 radially outwards ;  
    means forming an inner cylinder wall delimiting the  
stack radially inwards, whereby a central space is  
defined by the inner cylinder wall and an annular space  
is defined between the outer cylinder wall and the inner  
15 cylinder wall;  
    an end closure substantially adjoining the outer  
cylinder wall at one end of the stack;  
    means for blowing air through the central space  
towards the end closure and back through the annular  
20 space between the outer and inner cylinder walls for air-  
treatment of products carried by the conveyor belt in the  
helical path; and  
    means for conditioning the air blown through the  
annular space between the outer and inner cylinder walls.  
25 2. An apparatus as claimed in claim 1, wherein the  
end of the central space opposite the end closure is  
closed except for an inlet to the air-blowing means.  
3. An apparatus as claimed in claim 2, wherein the  
annular space between the outer and inner cylinder walls  
30 is open at the end opposite the end closure.  
4. An apparatus as claimed in claim 2 or 3, wherein  
the conditioning means is positioned in the central space  
within the inner cylinder wall.

5. An apparatus as claimed in claim 2 or 3, wherein the conditioning means is positioned outside a room having an inlet from the conditioning means and an outlet.

5        6. An apparatus as claimed in claim 1, further comprising a further end closure substantially adjoining the outer cylinder wall at the other end of the stack, whereby air is blown in a substantially closed path.

7. An apparatus as claimed in claim 6, wherein the  
10 conditioning means is positioned in the inner space within the inner cylinder wall.

8. An apparatus as claimed in claim 6, wherein the conditioning means is positioned in the further end closure.

15        9. An apparatus as claimed in claim 8, wherein the further end closure comprises a chamber having a first opening towards the annular space between the outer and inner cylinder walls and a second opening towards the central space within the inner cylinder wall.

20        10. An apparatus as claimed in claim 1, wherein the side plates of an underlying tier of the stack support the outer longitudinal edge of an overlying tier of the stack.

11. An apparatus as claimed in claim 1, wherein the  
25 conveyor belt has side plates at both of its longitudinal edges forming said outer and inner cylinder walls.

12. An apparatus as claimed in claim 11, wherein the side plates of an underlying tier of the stack support the corresponding longitudinal edge of an overlying tier  
30 of the stack.

1/3


FIG. 1  
PRIOR ART

FIG.2







FIG.3



**FIG.4**



**FIG.5**



## INTERNATIONAL SEARCH REPORT

International application No.

PCT/SE 99/00735

## A. CLASSIFICATION OF SUBJECT MATTER

IPC6: F25D 13/06, F25D 25/04, F25D 3/11, B65G 17/06, A23L 3/36  
According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC6: F25D, B65G, A23L

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	DE 1802699 A (J. & E. HALL LTD.), 14 August 1969 (14.08.69), figures 1,2, page 5, 3 paragraph - page 10 --	1,2,4,6,10, 11,12
Y	US 3938651 A (ALFRED ET AL), 17 February 1976 (17.02.76), column 2, line 59 - line 65, figures 2, 5A,5B --	1,2,4,6,10, 11,12
Y	US 4875343 A (JEPPSSON), 24 October 1989 (24.10.89), column 10, line 19 - line 30, figures 2,3,5,16 --	1,2,4,6,10, 11,12

☒ Further documents are listed in the continuation of Box C.☒ See patent family annex.

\* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&amp;" document member of the same patent family

Date of the actual completion of the international search

9 Sept 1999

Date of mailing of the international search report

10 -09- 1999

Name and mailing address of the ISA/  
Swedish Patent Office  
Box 5055, S-102 42 STOCKHOLM  
Facsimile No. +46 8 666 02 86

Authorized officer

Inger Löfving  
Telephone No. +46 8 782 25 00

## INTERNATIONAL SEARCH REPORT

International application No.

PCT/SE 99/00735

## C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	DE 835609 C (GESELLSCHAFT FÜR LINDE'S EISMASCHINEN A.-G.), 3 April 1952 (03.04.52), page 2, line 40 - line 44, figure 1 --	1-12
A	US 5205135 A (LANG), 27 April 1993 (27.04.93), fig 2,3and adherent text --	1-12
A	US 4798062 A (LIPINSKI ET AL), 17 January 1989 (17.01.89), column 7, line 49 - column 8, line 2, figure 12 --	1-12
A	WO 9116582 A1 (PALFRAMAN, JAMES ET AL), 31 October 1991 (31.10.91) -- -----	1-12



INTERNATIONAL SEARCH REPORT  
Information on patent family members

02/08/99

International application No.

PCT/SE 99/00735

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
DE 1802699 A	14/08/69	FR 1588664 A	17/04/70
US 3938651 A	17/02/76	AU 6642374 A	11/09/75
		BR 7401662 D	00/00/00
		CA 997702 A	28/09/76
		DE 2410392 A,C	12/09/74
		DK 134272 B,C	11/10/76
		FR 2220442 A,B	04/10/74
		GB 1420576 A	07/01/76
		IT 1007636 B	30/10/76
		JP 50026269 A	19/03/75
		NL 180402 B,C	16/09/86
		NL 7402777 A	10/09/74
		SE 381241 B,C	01/12/75
US 4875343 A	24/10/89	AT 83554 T	15/01/93
		DE 6890385 U	28/01/93
		DK 109389 A	15/09/89
		DK 172250 B	09/02/98
		EP 0333565 A,B	20/09/89
		SE 0333565 T3	
		GR 3006921 T	30/06/93
		WO 8908808 A	21/09/89
DE 835609 C	03/04/52	NONE	
US 5205135 A	27/04/93	AU 3070592 A	15/06/93
		CA 2122496 A	27/05/93
		US 5343715 A	06/09/94
		WO 9310410 A	27/05/93
US 4798062 A	17/01/89	NONE	

**INTERNATIONAL SEARCH REPORT**  
Information on patent family members

02/08/99

International application No.

PCT/SE 99/00735

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 9116582 A1	31/10/91	AT 125030 T	15/07/95
		AU 640007 B	12/08/93
		AU 7683291 A	11/11/91
		CA 2079471 A	18/10/91
		DE 69111230 D,T	16/11/95
		DK 525008 T	21/08/95
		EP 0525008 A,B	03/02/93
		SE 0525008 T3	
		ES 2074270 T	01/09/95
		US 5214934 A	01/06/93

---